



YDPU2.E305771 - TUBING, EXTRUDED INSULATING - COMPONENT

Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

RTE DI BRAMBILLA MASSIMO GIORGIO E C SNC

E305771

Via Borgo Roldi 49

26025 Pandino, Cr ITALY

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable Polyolefin tubing					
HF HALOGEN FREE	600	125	All except clear	-	Yes
Not heat shrinkable Polyvinyl Chloride (PVC) tubing					
PVC-UL	600	105	All except clear	01	Yes
Heat shrinkable Polyolefin tubing					
STP	600	125	All except clear	-	Yes
Flexible heat shrinkable Polyolefin tubing					
STP-BS	300	125	All except clear	-	Yes
Heat shrinkable Polyolefin tubing					
STP125	600	125	All except clear	-	Yes
Flexible heat shrinkable Polyolefin tubing					
STP125-BS	600	125	All except clear	-	Yes
STP125-F	600	125	All except clear	-	Yes
T3155	600	125	All except clear	-	Yes
Heat shrinkable Polyolefin tubing with adhesive liner					
TA3155	600	125	BK	-	Yes
TA4155	600	125	BK	-	Yes
Flexible heat shrinkable Polyolefin tubing					
TTP31	600	125	All except clear	-	No

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

Marking: Company name or tradename "E305771" , catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2017-11-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"



YDPU8.E305771 - TUBING, EXTRUDED INSULATING CERTIFIED FOR CANADA - COMPONENT

Tubing, Extruded Insulating Certified for Canada - Component

See General Information for Tubing, Extruded Insulating Certified for Canada - Component

RTE DI BRAMBILLA MASSIMO GIORGIO E C SNC

E305771

Via Borgo Roldi 49

26025 Pandino, Cr ITALY

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
Flexible heat shrinkable Polyolefin tubing					
HF HALOGEN FREE	600	125	All except clear	-	Yes
Not heat shrinkable Polyvinyl Chloride (PVC) tubing					
PVC-UL	600	105	All except clear	01	Yes
Heat shrinkable Polyolefin tubing					
STP	600	125	All except clear	-	Yes
Flexible heat shrinkable Polyolefin tubing					
STP-BS	300	125	All except clear	-	Yes
Heat shrinkable Polyolefin tubing					
STP125	600	125	All except clear	-	Yes
Flexible heat shrinkable Polyolefin tubing					
STP125-BS	600	125	All except clear	-	Yes
STP125-F	600	125	All except clear	-	Yes
T3155	600	125	All except clear	-	Yes
Heat shrinkable Polyolefin tubing with adhesive liner					
TA3155	600	125	BK	-	Yes
TA4155	600	125	BK	-	Yes
Flexible heat shrinkable Polyolefin tubing					
TTP31	600	125	All except clear	-	No

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

Marking: Company name or tradename "E305771" , catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius, date of manufacture (or traceable code) and the Recognized Component Mark for Canada,  printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2017-11-09

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"